



Bowers & Wilkins

HTM71 S3

Technical Information



Technical features

Decoupled Carbon Dome tweeter
Solid Body Tweeter-on-Top
Continuum™ cone FST midrange
Aerofoil™ Profile bass cones
Flowport™

Description

3-way vented-box system

Drive units

1x ø25mm (1in) Decoupled Carbon Dome high-frequency
1x ø130mm (5in) Continuum cone FST midrange
2x ø130mm (5in) Aerofoil Profile bass

Frequency range

45Hz to 33kHz

Frequency response

(+/-3dB from reference axis)

50Hz - 28kHz

Sensitivity

(on axis at 2.83Vrms at 1m)

89dB

Harmonic distortion

2nd and 3rd harmonics (90dB, 1m on axis)
<1% 90Hz - 22kHz
<0.5% 120Hz - 20kHz

Nominal impedance

8Ω (minimum 3.0Ω)

Recommended amplifier power

30W - 200W into 8Ω on unclipped programme

Max. recommended cable impedance

0.1Ω

Dimensions

Height: 165mm (6.5in) cabinet only
233mm (9.2in) including tweeter

Width: 628mm (24.7in) cabinet only

Depth: 318mm (12.5in) cabinet only
356mm (14in) including grille and terminals

Net weight

17.5kg (38.5lbs)

Finishes

Cabinet: Gloss black
Satin white
Mocha
Rosenut (APAC only)

Grille: Black
Grey (Satin White only)